



ALT - 900 DTM Acrylic

GENERAL: DTM Acrylic is a high performance, quick drying, direct to metal acrylic finish formulated for application to a wide variety of metals and other substrates, either direct or as a UV resistant finish applied over primer. ALT-900 DTM Acrylic is a water-based acrylic system that can be easily used as a non-hazardous water-soluble water repellent and rust preventative that is chemical and solvent resistant. **Black or Red color with additional colors or clear available.**

- Corrosion, chemical and fuel resistant
- Impact and abrasion resistant
- Flash/Early rust resistant
- Salt Fog ASTM B117 10B Rated
- For metal, wood and masonry substrates
- One or two coat protection
- Low VOC and low odor

SURFACE

PREPARATION: Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease or any other chemical stain spots. Lightly burn off excessive oil build up.

APPLICATION: Mix well before using. Normal use is full strength. Can be applied in a dip process or with a suitable spray machine, brush or roller.

COVERAGE: *Approximately 705-755 ft.² per gallon @ 1 mil dry*

CAUTION: **KEEP FROM FREEZING.** Wash tools in water. Use suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Keep out of the reach of children.

PACKAGING: 5 gallon pails, 55 gallon drums and 275/330 gallon tote tanks.

NOTE: Higher solids, density and viscosity may be required for full spray application. Contact your Allstates' Representative for additional instruction.

Material Specifications:

Requirements:

Weight per Gallon, ASTM D1010, (lbs).....	9.70 – 10.40
Viscosity @ 77°F ASTM D562 (Kreb's Stormer Unit).....	60 - 70 KU
% Nonvolatile by weight.....	49 - 56
Drying Time (min).....	<10 minutes @ 3mil
Application Temp (°F).....	45°F min.
Flammability.....	non-flammable
V.O.C. (lbs per gallon).....	<0.15 lbs/gal
HAPS.....	<1.2%